

IP NETWORK INTERCOM SLAVE STATION (EMERGENCY & SERVICE DUAL BUTTON) A-IPI-SL-12A

Description:

The IP Network Intercom Slave Station or dual button door station A-IPI-SL-12A is designed for two way duplex emergency communication system. Press the button to start the two way intercom call to the master station A-IP-RM-01, while recording, busy forward, sound pick up and pre-recorded announcement is also possible for this system. Control input and output is used to integrate with door access, CCTV or fire alarm system. Ideal for bank, factory, school, park, hospital and train station emergency help communication system.



Feature:

- Brushed aluminum design, Embedded installation.
- Dual button for emergency & service two way duplex intercom slave station
- Intercom panel built-in speaker, microphone.
- Full duplex two way communication system.
- Embed PC technology, built-in DSP & high speed industrial chip to ensure start time less than 1 second
- One short circuit output can be used for electronic access control or alarm indicator.
- One short circuit input can be used to play warning voice or trigger associated devices.
- Equipped with one local line output, capable of external active speakers or headphones for communication and receiving broadcasts.
- Equipped with one local line input, capable of external audio source equipment.
- Can achieve intercom and environmental sound monitoring with equipped IP microphone.
- Can be accessed from Ethernet ports and has cross network segment and cross routing functions.
- This device can support remote upgrades of both LAN/WAN networks.
- Aluminum finish can be durable use and waterproof rate level of IP54
- 1×RJ45 Ethernet Port, 12V DC power supply, POE power supply (optional)
- Ideal solution for prison, hospital, hotel, military, factory, train station and airport.



AYZO
SECURING BUSINESS SECURING LIVES

IP NETWORK INTERCOM SLAVE STATION (EMERGENCY & SERVICE DUAL BUTTON) A-IPI-SL-12A

Specification:

Model	A-IPI-SL-12A
Network interface	RJ45
Transmission Rate	10M/100Mbps
Audio Format	MP3/MP2
Sampling Rate	8K~48KHz
Audio Mode	16 digit stereo CD tone
SNR	≥75dB
Frequency response	200Hz—16KHz+-3dB
Input Sensitivity	10mv/250mv
Protocol	TCP/IP,UPP,IGMP, support group broadcasting
Harmonic Distortion	≤0.3%
Built in speaker	5W,8Ω
Line in	350MV、1KΩ
Line out	775MV、1KΩ
Control in	One short-circuit input
Control out	One short-circuit output
Operating Temperature	5°C ~ +45°C
Operating Humidity	10% ~ 90%
Power Supply	DC-12V
IP rate	IP54
Dimension	194.4×117×39.5mm
Power Consumption	≤8W

**IP NETWORK INTERCOM SLAVE STATION
(EMERGENCY & SERVICE DUAL BUTTON)
A-IPI-SL-12A**

System Connection Example:

IP Network Intercom Terminal Solution For Prison

